

View Online at <https://aerobasegroup.com/nsn/5930-00-739-6168>

Thread Class:

2a single mounting facility

Thread Length:

0.563 inches single mounting facility

Width Between Flats:

0.216 inches single actuator

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

9.407 inches

First Flat Length:

0.250 inches single actuator

Shaft Diameter:

0.312 inches single actuator

Shaft Length:

0.375 inches single actuator

Overall Diameter:

1.500 inches

Nonturn Device Radius:

0.625 inches at 12: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Pin at 12: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

3 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.500 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

0.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, parallel flatted, threaded hole single actuator

Terminal Type:

Connector, plug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

15.0 amperes resistive load dc at sea level

Style Designator:

Miniature, bushing mount

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0