

View Online at <https://aerobasegroup.com/nsn/5930-00-739-7072>

Thread Class:

2a single mounting facility

Thread Length:

0.455 inches single mounting facility and 0.485 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

Between 2.501 inches and 2.531 inches

First Flat Length:

0.425 inches single actuator and 0.455 inches single actuator

Flat Height:

0.201 inches single actuator and 0.231 inches single actuator

Shaft Diameter:

0.245 inches single actuator and 0.249 inches single actuator

Shaft Length:

0.985 inches single actuator and 1.015 inches single actuator

Overall Diameter:

Between 2.205 inches and 2.235 inches

Individual Section Quantity:

2

Nonturn Device Type:

Slotted bushing at 12: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

4 each section front

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Push to turn

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.469 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

0.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load dc at sea level and 2.5 amperes inductive load dc at sea level and 2.0 amperes lamp load dc at sea level

Special Features:

Dummy terminals at positions 6, 7 and 8

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0