NSN 5930-00-740-1089

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-740-1089

View Online at https://aerobasegroup.com/nsn/5930-00-740-1089
Hazardous Locations/environmental Protection:
Dustproof and vibration resistant and watertight
Overall Length:
5.188 inches
Overall Height:
5.687 inches
Overall Width:
2.812 inches
Body Height:
2.750 inches
Unthreaded Mounting Hole Diameter:
0.281 inches
Longest Horizontal Distance Between Mounting Centers:
2.406 inches
Shortest Horizontal Distance Between Mounting Centers:
0.656 inches
Longest Vertical Distance Between Mounting Centers:
3.281 inches
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Electrical access port
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Isosceles triangle
Terminal Type:
Screw
Contact Load Current Rating:
9.6 amperes inductive load eighth voltage
Contact Adjustability:
Actuation point adjustable
Contact Voltage Rating In Volts:
550.0 dc at sea level fifth voltage
Frequency In Hertz:
60.0 third voltage
Media For Which Designed:
Gas
Precious Material And Location:
Contacts silver
Precious Material:

Silver

NSN 5930-00-740-1089

Thermostatic Switch - Page 2 of 2



Style Designator:
Rectangular
Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0