

View Online at <https://aerobasegroup.com/nsn/5930-00-740-3085>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Submersible

Body Diameter:

1.250 inches

Bushing Length:

0.500 inches

Body Length:

1.550 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

Between 0.122 inches and 0.123 inches

Actuator Height:

0.250 inches

Actuator Free Position Height:

0.921 inches

Maximum Voltage Rating In Volts:

30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, permanent jumper with no external terminal, one position momentary single switch unit

Switch Release Force:

20.0 inch-ounces

Switch Actuating Force:

Between 42.0 inch-ounces and 50.0 inch-ounces

Actuator Movement:

Between 0.062 pretravel inches and 0.125 overtravel inches and 0.033 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0