# NSN 5930-00-751-7808

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-751-7808

# Thread Class:

2a single mounting facility

# Thread Length:

0.313 inches single mounting facility

# Hazardous Locations/environmental Protection:

Dustproof

# **Overall Length:**

2.553 inches

# **Overall Height:**

1.750 inches

**Overall Width:** 

1.750 inches

## Shaft Diameter:

0.250 inches single actuator

## Shaft Length:

1.000 inches single actuator

# Individual Section Quantity:

3

#### Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

1 each section rear

#### Throw Quantity:

11 each section rear

## **Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

## **Contact Voltage Rating In Volts:**

125.0 ac at sea level

## Switch Actuator Indexing Position Quantity:

11 single actuator

#### Shaft Type:

Round single actuator

#### **Terminal Type:**

Tab, solder lug

## **Contact Switching Action:**

Breaks before makes each section rear

## Switch Actuator Positioning Increment:

30.0 degrees single actuator

### Switch Actuator Stop Device Type:

Fixed stop single actuator

# NSN 5930-00-751-7808

Rotary Switch - Page 2 of 2



**Contact Load Current Rating:** 

5.0 amperes resistive load ac at sea level

#### **Precious Material And Location:**

Contacts and collector rings and wiper arms and terminals silver

**Precious Material:** 

Silver

Style Designator:

Tap, square frame

#### Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0