

View Online at <https://aerobasegroup.com/nsn/5930-00-751-9791>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.375 inches single mounting facility

**Overall Length:**

5.530 inches

**Overall Height:**

1.484 inches

**Overall Width:**

1.438 inches

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

2.250 inches single actuator

**Nonturn Device Radius:**

0.438 inches at 9: 00 o'clock

**Individual Section Quantity:**

5

**Knob Manufacturer Code:**

71590

**Knob Manufacturer Part Number:**

P-120

**Nonturn Device Type:**

Tab at 9: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

12 each section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Features Provided:**

Actuator knob

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

6.0 lowest dc voltage rating at sea level

**Rotor Through Connection Quantity:**

1 each section

**Switch Actuator Indexing Position Quantity:**

12 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Makes before breaks each section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

5.5 amperes resistive load highest dc voltage rating at sea level

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0