## NSN 5930-00-752-2630

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-752-2630

**Thread Class:** 

2a single mounting facility

**Thread Length:** 

0.375 inches single mounting facility

**Overall Length:** 

3.125 inches

**Overall Height:** 

Between 1.448 inches and 1.500 inches

**Overall Width:** 

1.312 inches

**Shaft Diameter:** 

0.248 inches single actuator and 0.252 inches single actuator

**Shaft Length:** 

2.250 inches single actuator

**Nonturn Device Radius:** 

0.438 inches at 9: 00 o'clock

**Individual Section Quantity:** 

1

**Nonturn Device Type:** 

Tab at 9: 00 o'clock

**Operating Tempurature Range:** 

-55.0/+85.0 degrees celsius

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

1 single section rear

**Throw Quantity:** 

12 single section front

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

15.0 dc at sea level

**Rotor Through Connection Quantity:** 

1 single section

**Switch Actuator Indexing Position Quantity:** 

12 single actuator

Shaft Type:

Round single actuator

**Criticality Code Justification:** 

Feat

## **NSN 5930-00-752-2630**Rotary Switch - Page 2 of 2



Terminal Type:
Tab, solder lug
Contact Switching Action:
Breaks before makes single section rear
Switch Actuator Positioning Increment:
30.0 degrees single actuator
Switch Actuator Stop Device Type:
Adjustable stop single actuator
Contact Load Current Rating:
2.0 amperes resistive load dc at sea level
Special Features:
Weapons system essential
Style Designator:
Circular wafer, bushing mount
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A052b0