NSN 5930-00-752-2630

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-752-2630

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Length:

3.125 inches

Overall Height:

Between 1.448 inches and 1.500 inches

Overall Width:

1.312 inches

Shaft Diameter:

0.248 inches single actuator and 0.252 inches single actuator

Shaft Length:

2.250 inches single actuator

Nonturn Device Radius:

0.438 inches at 9: 00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 9: 00 o'clock

Operating Tempurature Range:

-55.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

12 single section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

15.0 dc at sea level

Rotor Through Connection Quantity:

1 single section

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Round single actuator

Criticality Code Justification:

Feat

NSN 5930-00-752-2630

Rotary Switch - Page 2 of 2



Terminal Type: Tab, solder lug **Contact Switching Action:** Breaks before makes single section rear Switch Actuator Positioning Increment: 30.0 degrees single actuator Switch Actuator Stop Device Type: Adjustable stop single actuator **Contact Load Current Rating:** 2.0 amperes resistive load dc at sea level **Special Features:** Weapons system essential Style Designator: Circular wafer, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A052b0