

View Online at <https://aerobasegroup.com/nsn/5930-00-752-2766>

Body Style:

Hole mount

Overall Length:

2.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 1.796 inches and 1.828 inches

Overall Width:

0.969 inches

Body Length:

Between 2.219 inches and 2.281 inches

Body Width:

Between 0.938 inches and 1.000 inches

Body Height:

Between 1.594 inches and 1.656 inches

Actuator Style:

Round

Actuator Height:

Between 0.719 inches and 0.781 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Maximum Voltage Rating In Volts:

24.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.164 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

25.000 amperes resistive dc and 15.000 amperes inductive dc and 6.000 amperes lamp dc

Test Data Document:

81349-mil-s-13735 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Terminal Type And Quantity:

1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0