NSN 5930-00-752-2795

Push Switch - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/5930-00-752-2795

| Bushing mounted |
|--|
| Overall Length: |
| 0.780 inches |
| Overall Height: |
| 1.480 inches |
| Overall Width: |
| 0.906 inches |
| Bushing Length: |
| 0.300 inches |
| Body Length: |
| 0.780 inches |
| Body Width: |
| 0.906 inches |
| Body Height: |
| 0.950 inches |
| Case Material: |
| Plastic |
| Actuator Diameter: |
| 0.323 inches |
| Actuator Height: |
| 0.190 inches |
| Actuator Color: |
| Black single actuator |
| Maximum Voltage Rating In Volts: |
| 250.0 ac and 30.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded bushing |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.469 inches |
| Nonpile-up Contact Arrangement: |
| 3 pole, double throw, one position momentary single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac |
| Special Features: |
| Phenolic body insulation rated for 250 f |
| Thread Series Designator: |
| Uns |
| |

NSN 5930-00-752-2795

Push Switch - Page 2 of 2



| i ei ii ii iai Tybe And Quantity. | Tε | rminal | Type | And | Quantity: | |
|-----------------------------------|----|--------|------|-----|-----------|--|
|-----------------------------------|----|--------|------|-----|-----------|--|

9 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0