NSN 5930-00-752-4599

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-752-4599

| Thread Len | gth: |
|------------|------|
|------------|------|

0.563 inches single threaded bushing

Hazardous Locations/environmental Protection:

Waterproof and corrosion resistant and fungus resistant

Overall Length:

4.000 inches

Body Length:

1.375 inches

Overall Diameter:

2.219 inches

Pressure Switch Type:

Gage

Width Across Flats:

0.875 inches

Mounting Method:

Inlet connection

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.250 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

5.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point not adjustable

Contact Stimulus Rating:

9.00 actuation point pounds per square inch and 13.00 actuation point pounds per square inch

Contact Voltage Rating In Volts:

32.0 dc at sea level single voltage

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Test Data Document:

81349-mils12211 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Nptf single pressure connection

NSN 5930-00-752-4599

Pressure Switch - Page 2 of 2



| _ | | | | | |
|---|----|------|---|--------|--|
| c | hο | JIF. | | .ife: | |
| J | | | _ | .II C. | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0