# NSN 5930-00-755-0760



Pressure Switch - Page 1 of 2	oup
View Online at https://aerobasegroup.com/nsn/5930-00-755-0760	
Overall Length:	
4.125 inches	
Overall Height:	
1.500 inches	
Overall Width:	
1.500 inches	
Body Length:	
2.531 inches	
Unthreaded Mounting Hole Diameter:	
0.210 inches	
Longest Horizontal Distance Between Mounting Centers:	
1.125 inches	
Longest Vertical Distance Between Mounting Centers:	
1.125 inches	
Pressure Switch Type:	
Gage	
Mounting Method:	
Base and unthreaded hole	
Features Provided:	
Tamper proof cap	
Thready Qty Per Inch (tpi):	
24 single pressure connection	
Contact Action Stimulus:	
Increase	
Proof Pressure:	
4500.00 pounds per square inch	
Thread Size:	
0.625 inches single pressure connection	
Mounting Facility Pattern:	
Four position rectangular	
Nonpile-up Contact Arrangement:	
1 pole, double throw, one position momentary	
Terminal Type:	
Connector, receptacle	
Contact Load Current Rating:	
4.0 amperes resistive load single voltage	
Contact Adjustability:	
Deactuation point not adjustable and actuation point not adjustable	
Contact Stimulus Rating:	
2900.00 actuation point pounds per square inch gage and 2500.00 deactuation point pounds per square inch gage and 400.00 differer	ntial
point pounds per square inch gage	

#### **Contact Voltage Rating In Volts:**

30.0 dc at sea level single voltage

## NSN 5930-00-755-0760

Pressure Switch - Page 2 of 2



Pressure Connector Type:

Double compression, threaded internal single connection

#### Media For Which Designed:

Liquid

Style Designator:

Rectangular

## Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A048b0