## NSN 5930-00-755-0760

Pressure Switch - Page 1 of 2

Contact Voltage Rating In Volts: 30.0 dc at sea level single voltage



View Online at https://aerobasegroup.com/nsn/5930-00-755-0760

Overall Length:
4.125 inches
Overall Height:
1.500 inches
Overall Width:
1.500 inches
Body Length:
2.531 inches
Unthreaded Mounting Hole Diameter:
0.210 inches
Longest Horizontal Distance Between Mounting Centers:
1.125 inches
Longest Vertical Distance Between Mounting Centers:
1.125 inches
Pressure Switch Type:
Gage
Mounting Method:
Base and unthreaded hole
Features Provided:
Tamper proof cap
Thready Qty Per Inch (tpi):
24 single pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
4500.00 pounds per square inch
Thread Size:
0.625 inches single pressure connection
Mounting Facility Pattern:
Four position rectangular
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Connector, receptacle
Contact Load Current Rating:
4.0 amperes resistive load single voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
2900.00 actuation point pounds per square inch gage and 2500.00 deactuation point pounds per square inch gage and 400.00 differential
point pounds per square inch gage

## NSN 5930-00-755-0760

Pressure Switch - Page 2 of 2

Fiig: A048b0



Pressure Connector Type:
Double compression, threaded internal single connection
Media For Which Designed:
Liquid
Style Designator:
Rectangular
Thread Series Designator:
Unf single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No