

View Online at <https://aerobasegroup.com/nsn/5930-00-755-0761>

Thread Length:

0.375 inches single pressure connection

Hazardous Locations/environmental Protection:

Waterproof

Overall Length:

2.078 inches

Outside Diameter:

0.125 inches single connection

Body Length:

1.813 inches

Overall Diameter:

1.095 inches

Pressure Switch Type:

Gage

Width Across Flats:

1.000 inches

Mounting Method:

Inlet connection

Contact Action Stimulus:

Increase

Thread Size:

0.125 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

3.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable, manual reset and actuation point not adjustable

Contact Stimulus Rating:

40.00 actuation point pounds per square inch gage and 110.00 actuation point pounds per square inch gage

Contact Voltage Rating In Volts:

24.0 dc at sea level single voltage

Pressure Connector Type:

Plain, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Test Data Document:

81349-mils12211 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Nptf single pressure connection

Specification Data:

96906-ms75063-1 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0