

View Online at <https://aerobasegroup.com/nsn/5930-00-755-2191>

Thread Class:

2a single threaded stud

Thread Length:

0.500 inches single threaded stud

Overall Length:

5.407 inches

Overall Height:

1.250 inches

Overall Width:

1.531 inches

Body Length:

2.000 inches

Operating Temperature Rating:

130.0 degrees fahrenheit and -30.0 degrees fahrenheit

Mounting Method:

Threaded stud

Thready Qty Per Inch (tpi):

32 single threaded stud

Contact Action Stimulus:

Increase

Thread Size:

0.190 inches single threaded stud

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

5.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

1000.00 actuation point feet per minute and 750.00 actuation point feet per minute and 800.00 actuation point feet per minute and 700.00 deactuation point feet per minute and 400.00 deactuation point feet per minute and 500.00 deactuation point feet per minute and 300.00 differential point feet per minute and 250.00 differential point feet per minute and 300.00 differential point feet per minute

Contact Voltage Rating In Volts:

250.0 ac at sea level single voltage

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Rectangular

Thread Series Designator:

Unc single threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A048b0