

View Online at <https://aerobasegroup.com/nsn/5930-00-755-2191>

**Thread Class:**

2a single threaded stud

**Thread Length:**

0.500 inches single threaded stud

**Overall Length:**

5.407 inches

**Overall Height:**

1.250 inches

**Overall Width:**

1.531 inches

**Body Length:**

2.000 inches

**Operating Temperature Rating:**

130.0 degrees fahrenheit and -30.0 degrees fahrenheit

**Mounting Method:**

Threaded stud

**Thready Qty Per Inch (tpi):**

32 single threaded stud

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.190 inches single threaded stud

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

5.0 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

1000.00 actuation point feet per minute and 750.00 actuation point feet per minute and 800.00 actuation point feet per minute and 700.00 deactuation point feet per minute and 400.00 deactuation point feet per minute and 500.00 deactuation point feet per minute and 300.00 differential point feet per minute and 250.00 differential point feet per minute and 300.00 differential point feet per minute

**Contact Voltage Rating In Volts:**

250.0 ac at sea level single voltage

**Frequency In Hertz:**

60.0 single voltage

**Media For Which Designed:**

Gas

**Precious Material And Location:**

Contact surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Rectangular

**Thread Series Designator:**

Unc single threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A048b0