

View Online at <https://aerobasegroup.com/nsn/5930-00-755-2972>

Thread Class:

2a single mounting facility

Thread Length:

0.215 inches single mounting facility and 0.221 inches single mounting facility

Overall Length:

Between 3.047 inches and 3.077 inches

Overall Height:

0.938 inches

First Flat Length:

0.505 inches single actuator and 0.515 inches single actuator

Flat Height:

0.215 inches single actuator and 0.221 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.251 inches single actuator

Shaft Length:

2.235 inches single actuator and 2.265 inches single actuator

Overall Diameter:

1.188 inches

Nonturn Device Radius:

0.365 inches at 3:00 o'clock and 0.385 inches at 3:00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 3:00 o'clock

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

4 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

135.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

335.0 milliamperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0