

View Online at <https://aerobasegroup.com/nsn/5930-00-755-3266>

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Overall Length:

2.252 inches

Overall Height:

1.125 inches

Overall Width:

0.937 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.125 inches single actuator

Shaft Diameter:

0.188 inches single actuator

Shaft Length:

0.938 inches single actuator

Nonturn Device Radius:

0.375 inches at 9: 00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 9: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical and nonpile-up nonsymmetrical

Pole Quantity:

1 2nd section front

Throw Quantity:

4 2nd section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

90.0 degrees from nonturn device single actuator

Rotor Through Connection Quantity:

1 1st section

Switch Actuator Indexing Position Quantity:

12 all actuators

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes 2nd section front

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Detent Rotational Torque Range:

+12.000/+25.000 inch-ounces single actuator

Switch Actuator Stop Device Type:

Fixed stop all actuators

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Special Features:

Section 1 has 10 throws on front and 1 throw on rear

Precious Material And Location:

Contacts and rotor blades silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0