

View Online at <https://aerobasegroup.com/nsn/5930-00-755-3316>

Thread Class:

3a single pressure connection

Overall Length:

3.000 inches

Outside Diameter:

0.438 inches single connection

Body Diameter:

1.375 centimeters

Body Length:

2.125 inches

Overall Diameter:

1.375 inches

Unthreaded Mounting Hole Diameter:

0.201 inches

Distance Between Mounting Facility Centers:

0.500 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit

Mounting Method:

Flange and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Proof Pressure:

1000.00 pounds per square inch gage

Thread Size:

0.438 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

2500.00 pounds per square inch gage

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

4.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable, preset

Contact Adjustment Range:

+6.00/+25.00 actuation point pounds per square inch gage

Contact Adjustment Type:

Internal actuation point screw

Contact Stimulus Rating:

7.00 actuation point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Gasket seal, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0