## NSN 5930-00-755-3515

Pull Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-755-3515 **Thread Class:** 2a **Body Style: Bushing mounted Hazardous Locations/environmental Protection:** Fungus proof and moisture proof **Body Diameter:** 0.938 inches **Bushing Length:** 0.375 inches **Body Length:** 1.594 inches **Actuator Style:** Round **Actuator Diameter:** 1.250 inches **Actuator Height:** 0.969 inches **Actuator Color:** Red single actuator **Maximum Voltage Rating In Volts:** 28.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded bushing **Features Provided:** Holding solenoid Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.625 inches **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 10.000 amperes resistive dc **Thread Series Designator:** Un **Terminal Type And Quantity:** 4 screw

N/a

Shelf Life:

## **NSN 5930-00-755-3515**Pull Switch - Page 2 of 2



	Of			

Demilitarization:

No

Fiig:

A053a0