NSN 5930-00-755-3589

Rotary Switch Section - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5930-00-755-3589 |
|---|
| Overall Height: |
| 2.312 inches |
| Overall Width: |
| 1.750 inches |
| Body Thickness: |
| 0.062 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.125 inches single mounting facility |
| Longest Horizontal Distance Between Mounting Centers: |
| 2.000 inches single mounting facility |
| Operating Tempurature Range: |
| -55.0/+100.0 degrees celsius |
| Switch Contact Basic Design: |
| Nonpile-up symmetrical |
| Pole Quantity: |
| 1 single section front |
| Throw Quantity: |
| 5 single section front |
| Mounting Method: |
| Strut single mounting facility and unthreaded hole single mounting facility |
| Contact Voltage Rating In Volts: |
| 28.0 dc at sea level |
| Rotor Through Connection Quantity: |
| 1 single section |
| Mounting Facility Pattern: |
| Two position in-line single mounting facility |
| Terminal Type: |
| Tab, solder lug |
| Contact Switching Action: |
| Breaks before makes single section rear |
| Contact Load Current Rating: |
| 1.0 amperes resistive load ac at sea level |
| Special Features: |
| Color coded with red dot to indicate top front |
| Precious Material And Location: |
| Rotor blades and terminals silver |
| Precious Material: |
| Silver |
| Style Designator: |
| Switch section, rotary |
| Shelf Life: |

N/a

NSN 5930-00-755-3589

Rotary Switch Section - Page 2 of 2



| | | | ure: | |
|--|--|--|------|--|
| | | | | |
| | | | | |

--

Demilitarization:

No

Fiig:

A052b0