

View Online at <https://aerobasegroup.com/nsn/5930-00-755-3717>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Length:

5.344 inches

Overall Height:

1.312 inches

Overall Width:

1.297 inches

First Flat Length:

0.406 inches single actuator

Flat Height:

0.188 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.250 inches single actuator

Shaft Length:

0.469 inches single actuator

Nonturn Device Radius:

0.531 inches at 3:00 o'clock

Individual Section Quantity:

15

Nonturn Device Type:

Tab at 3:00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

8 4th section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

30.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Clip

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load ac at sea level

Special Features:

2section 6 has 4 dummy terminals on rear; section 9 has 2 dummy terminals on rear; section 10 has 3 dummy terminals on rear; section 13 has 7 throws and 1 dummy terminal on rear; section 14 has 2 throws on rear; section 15 has 8 throws on rear

Precious Material And Location:

Contacts and rotor blades silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0