

View Online at <https://aerobasegroup.com/nsn/5930-00-755-3756>

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Overall Length:

2.563 inches

Overall Height:

1.031 inches

Overall Width:

1.250 inches

First Flat Length:

0.375 inches single actuator

Flat Height:

0.156 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.188 inches single actuator

Nonturn Device Radius:

0.531 inches at 9: 00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 9: 00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

10 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load dc at sea level

Precious Material And Location:

Contacts and rotors silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0