

View Online at <https://aerobasegroup.com/nsn/5930-00-755-3935>

**Thread Length:**

0.430 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

2.140 inches

**First Flat Length:**

0.250 inches single actuator

**Flat Height:**

0.188 inches single actuator

**Shaft Length:**

0.700 inches single actuator

**Overall Diameter:**

1.040 inches

**Nonturn Device Radius:**

0.550 inches at 3:00 o'clock

**Individual Section Quantity:**

2

**Nonturn Device Type:**

Pin at 3:00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

9 each section front

**Mounting Method:**

Threaded bushing single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Shaft Flat/slot Angular Location:**

0.0 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:**

10 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Makes before breaks each section front

**Switch Actuator Positioning Increment:**

36.0 degrees single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load ac at sea level

**Style Designator:**

Circular wafer, bushing mount

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0