

View Online at <https://aerobasegroup.com/nsn/5930-00-755-4481>

Thread Class:

2a single mounting facility

Thread Length:

0.469 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof and explosion proof

First Flat Length:

0.375 inches single actuator

Flat Height:

0.188 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.000 inches single actuator

Individual Section Quantity:

1

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

3 single section rear

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Metallic inclosure

Thread Size:

0.469 inches single mounting facility

Contact Voltage Rating In Volts:

250.0 ac at sea level

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

6.0 amperes resistive load ac at sea level

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0