

View Online at <https://aerobasegroup.com/nsn/5930-00-755-5133>

**Thread Class:**

2a single pressure connection

**Hazardous Locations/environmental Protection:**

Vibration resistant

**Overall Length:**

5.563 inches

**Outside Diameter:**

0.438 inches single connection

**Overall Height:**

2.562 inches

**Overall Width:**

3.156 inches

**Body Length:**

4.625 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Input port

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

280.00 pounds per square inch

**Thread Size:**

0.438 inches single pressure connection

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

5.0 amperes resistive load first voltage

**Contact Adjustability:**

Actuation point adjustable

**Contact Adjustment Range:**

+0.00/+140.00 actuation point pounds per square inch

**Contact Adjustment Type:**

External actuation point screw

**Contact Voltage Rating In Volts:**

600.0 ac at sea level second voltage

**Pressure Connector Type:**

Flared, threaded external single connection

**Media For Which Designed:**

Gas or liquid

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

Rectangular

**Thread Series Designator:**

Unf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0