

View Online at <https://aerobasegroup.com/nsn/5930-00-755-5843>

Overall Length:

5.187 inches

Overall Height:

2.875 inches

Overall Width:

4.375 inches

First Flat Length:

0.500 inches single actuator

Flat Height:

0.312 inches single actuator

Shaft Diameter:

0.375 inches single actuator

Shaft Length:

0.875 inches single actuator

Individual Section Quantity:

8

Knob Manufacturer Code:

82121

Knob Manufacturer Part Number:

8164-12y

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

3 each section front

Mounting Facility Circle Radius:

1.609 inches single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

20 single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Switch Actuator Momentary Position:

Clockwise single actuator

Shaft Flat/slot Angular Location:

180.0 degrees from nonturn device single actuator

Mounting Facility Pattern:

Four position circular single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted, threaded hole single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Special Features:

Shaft drilled perpendicular to flat and tapped 5-40 0.438 in. From end of shaft for pin style 1 mounting 2 holes 0.312 in. On 3.812 in. Mounting centers

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc single mounting facility

Reference Number Differentiating Characteristics:

Material will be in accordance with ships parts control centeractivity hx quality control, manufacturing and testing specifications

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A052b0