# NSN 5930-00-755-5936

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-755-5936

#### **Overall Length:**

3.905 inches

# **Overall Height:**

2.125 inches

# **Overall Width:**

1.812 inches

#### First Flat Length:

0.500 inches single actuator

#### Flat Height:

0.218 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.562 inches single actuator

#### **Unthreaded Mounting Hole Diameter:**

#### 0.188 inches single mounting facility

#### **Individual Section Quantity:**

7

# Longest Horizontal Distance Between Mounting Centers:

1.437 inches single mounting facility

# Longest Vertical Distance Between Mounting Centers:

1.750 inches single mounting facility

#### Switch Contact Basic Design:

Nonpile-up symmetrical

#### Pole Quantity:

1 each section periphery

#### **Throw Quantity:**

4 each section periphery

#### Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

#### Contact Voltage Rating In Volts:

30.0 dc at sea level

#### **Mounting Facility Pattern:**

Four position rectangular single mounting facility

#### Switch Actuator Indexing Position Quantity:

4 single actuator

# Shaft Type:

Round, flatted single actuator

# **Terminal Type:**

Tab w/screw

#### **Contact Switching Action:**

Breaks before makes each section periphery

# NSN 5930-00-755-5936

Rotary Switch - Page 2 of 2



# Switch Actuator Positioning Increment:

45.0 degrees single actuator

#### Switch Actuator Stop Device Type:

Fixed stop single actuator

# **Contact Load Current Rating:**

5.0 amperes resistive load dc at sea level and 2.5 amperes inductive load dc at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0