

View Online at <https://aerobasegroup.com/nsn/5930-00-755-6157>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.187 inches

Body Length:

1.530 inches

Body Width:

1.040 inches

Body Height:

2.090 inches

Unthreaded Mounting Hole Diameter:

0.166 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.125 inches

Actuator Style:

Round

Actuator Diameter:

1.040 inches

Actuator Height:

0.375 inches

Actuator Free Position Height:

2.406 inches

Maximum Voltage Rating In Volts:

30.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

8.0 ounces

Switch Actuating Force:

80.0 ounces

Actuator Movement:

Between 0.078 pretravel inches and 0.250 overtravel inches and 0.031 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 10.000 amperes inductive dc and 6.000 amperes motor dc

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0