## NSN 5930-00-755-6157

**Hazardous Locations/environmental Protection:** 

Sensitive Switch - Page 1 of 2

**Body Style:**Hole mounted

Dustproof



View Online at https://aerobasegroup.com/nsn/5930-00-755-6157

**Center To Center Distance Between Mounting Facilities Parallel To Length:** 

1.187 inches
Body Length:
1.530 inches
Body Width:
1.040 inches
Body Height:
2.090 inches
Unthreaded Mounting Hole Diameter:
0.166 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.125 inches
Actuator Style:
Round
Actuator Diameter:
1.040 inches
Actuator Height:
0.375 inches
Actuator Free Position Height:
2.406 inches
Maximum Voltage Rating In Volts:
30.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Switch Release Force:
8.0 ounces
Switch Actuating Force:
80.0 ounces
Actuator Movement:
Between 0.078 pretravel inches and 0.250 overtravel inches and 0.031 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
10.000 amperes resistive dc and 10.000 amperes inductive dc and 6.000 amperes motor dc
Precious Material And Location:
Contacts silver
Terminal Type And Quantity:
6 screw

## NSN 5930-00-755-6157

Sensitive Switch - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0