

View Online at <https://aerobasegroup.com/nsn/5930-00-755-6157>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.187 inches

**Body Length:**

1.530 inches

**Body Width:**

1.040 inches

**Body Height:**

2.090 inches

**Unthreaded Mounting Hole Diameter:**

0.166 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

1.125 inches

**Actuator Style:**

Round

**Actuator Diameter:**

1.040 inches

**Actuator Height:**

0.375 inches

**Actuator Free Position Height:**

2.406 inches

**Maximum Voltage Rating In Volts:**

30.0 dc

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

8.0 ounces

**Switch Actuating Force:**

80.0 ounces

**Actuator Movement:**

Between 0.078 pretravel inches and 0.250 overtravel inches and 0.031 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 10.000 amperes inductive dc and 6.000 amperes motor dc

**Precious Material And Location:**

Contacts silver

**Terminal Type And Quantity:**

6 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0