

View Online at <https://aerobasegroup.com/nsn/5930-00-755-6560>

Thread Class:

2a single mounting facility

Thread Length:

0.188 inches single mounting facility

Overall Length:

1.438 inches

First Flat Length:

0.312 inches single actuator

Flat Height:

0.188 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.438 inches single actuator

Overall Diameter:

0.750 inches

Nonturn Device Radius:

0.265 inches at 11:30 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Pin at 11:30 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

3 single section rear

Throw Quantity:

4 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

300.0 highest dc voltage rating at sea level

Shaft Flat/slot Angular Location:

180.0 degrees from contact position 1 single actuator

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load lowest ac voltage rating at sea level

Style Designator:

Snap or line

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0