NSN 5930-00-755-6634

Rotary Switch Section - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-755-6634

| Overa | ш | Dia | me | ter | ٠. |
|-----------|---|-----|----|---|----|
| O 4 C 1 G | | DIG | | ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,, | |

Between 1.515 inches and 1.547 inches

Body Thickness:

Between 0.060 inches and 0.064 inches

Unthreaded Mounting Hole Diameter:

0.253 inches single mounting facility

Longest Horizontal Distance Between Mounting Centers:

1.245 inches single mounting facility and 1.255 inches single mounting facility

Operating Tempurature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

3 single section rear

Mounting Facility Circle Radius:

0.115 inches single mounting facility

Mounting Method:

Strut single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Rotor Through Connection Quantity:

1 single section

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks single section rear

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Style Designator:

Switch section, rotary

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A052b0