# NSN 5930-00-755-6634

Rotary Switch Section - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-755-6634

Overa	ш	Dia	am	ete	r-
O 4 C 1 G		$\boldsymbol{\nu}$	4111	$-\iota -$	

Between 1.515 inches and 1.547 inches

### **Body Thickness:**

Between 0.060 inches and 0.064 inches

# **Unthreaded Mounting Hole Diameter:**

0.253 inches single mounting facility

### **Longest Horizontal Distance Between Mounting Centers:**

1.245 inches single mounting facility and 1.255 inches single mounting facility

# **Operating Tempurature Range:**

-65.0/+85.0 degrees celsius

### **Switch Contact Basic Design:**

Nonpile-up symmetrical

### **Pole Quantity:**

1 single section rear

### **Throw Quantity:**

3 single section rear

### **Mounting Facility Circle Radius:**

0.115 inches single mounting facility

# **Mounting Method:**

Strut single mounting facility

# **Contact Voltage Rating In Volts:**

28.0 dc at sea level

### **Rotor Through Connection Quantity:**

1 single section

# **Terminal Type:**

Tab, solder lug

# **Contact Switching Action:**

Makes before breaks single section rear

### **Contact Load Current Rating:**

1.0 amperes resistive load ac at sea level

# Style Designator:

Switch section, rotary

# Shelf Life:

N/a

### **Unit Of Measure:**

--

### **Demilitarization:**

Yes - demil/mli

### Fiig:

A052b0