

View Online at <https://aerobasegroup.com/nsn/5930-00-755-7037>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.370 inches single mounting facility and 0.380 inches single mounting facility

**Overall Length:**

Between 3.402 inches and 3.504 inches

**Overall Height:**

Between 1.526 inches and 1.536 inches

**Overall Width:**

Between 1.307 inches and 1.317 inches

**First Flat Length:**

0.390 inches single actuator and 0.430 inches single actuator

**Flat Height:**

0.216 inches single actuator and 0.220 inches single actuator

**Shaft Diameter:**

0.245 inches single actuator and 0.250 inches single actuator

**Shaft Length:**

0.858 inches single actuator and 0.862 inches single actuator

**Nonturn Device Radius:**

0.370 inches at 3:00 o'clock and 0.380 inches at 3:00 o'clock

**Individual Section Quantity:**

2

**Nonturn Device Type:**

Tab at 3:00 o'clock

**Operating Temperature Range:**

-55.0/+100.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

2 each section rear

**Throw Quantity:**

3 each section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

15.0 dc at sea level

**Shaft Flat/slot Angular Location:**

45.0 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Makes before breaks each section front

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Detent Rotational Torque Range:**

+30.000/+45.000 inch-ounces single actuator

**Switch Actuator Stop Device Type:**

Fixed stop-breakoff tab single actuator

**Contact Load Current Rating:**

0.1 amperes resistive load ac at sea level

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0