NSN 5930-00-755-7037

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-755-7037

Thread Class:

2a single mounting facility

Thread Length:

0.370 inches single mounting facility and 0.380 inches single mounting facility

Overall Length:

Between 3.402 inches and 3.504 inches

Overall Height:

Between 1.526 inches and 1.536 inches

Overall Width:

Between 1.307 inches and 1.317 inches

First Flat Length:

0.390 inches single actuator and 0.430 inches single actuator

Flat Height:

0.216 inches single actuator and 0.220 inches single actuator

Shaft Diameter:

0.245 inches single actuator and 0.250 inches single actuator

Shaft Length:

0.858 inches single actuator and 0.862 inches single actuator

Nonturn Device Radius:

0.370 inches at 3: 00 o'clock and 0.380 inches at 3: 00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 3: 00 o'clock

Operating Tempurature Range:

-55.0/+100.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section rear

Throw Quantity:

3 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

15.0 dc at sea level

Shaft Flat/slot Angular Location:

45.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

4 single actuator

NSN 5930-00-755-7037

Rotary Switch - Page 2 of 2



Shaft Type:
Round, flatted single actuator
Terminal Type:
Tab, solder lug
Contact Switching Action:
Makes before breaks each section front
Switch Actuator Positioning Increment:
30.0 degrees single actuator
Detent Rotational Torque Range:
+30.000/+45.000 inch-ounces single actuato
Switch Actuator Stop Device Type:
Fixed stop-breakoff tab single actuator
Contact Load Current Rating:
0.1 amperes resistive load ac at sea level
Style Designator:
Circular wafer, bushing mount
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A052b0