

View Online at <https://aerobasegroup.com/nsn/5930-00-755-7045>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Length:

1.687 inches

Overall Height:

1.328 inches

Overall Width:

1.625 inches

First Flat Length:

0.375 inches single actuator

Flat Height:

0.218 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.812 inches single actuator

Nonturn Device Radius:

0.063 inches at 3:00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Tab at 3:00 o'clock

Operating Temperature Range:

-40.0/+75.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section front

Throw Quantity:

3 single section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

0.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section front

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0