

View Online at <https://aerobasegroup.com/nsn/5930-00-756-0355>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Length:

6.500 inches

Overall Height:

2.310 inches

Overall Width:

1.970 inches

Shaft Diameter:

0.250 inches 1st actuator

Shaft Length:

0.500 inches 2nd actuator

Nonturn Device Radius:

0.530 inches at 10: 30 o'clock

Individual Section Quantity:

4

Nonturn Device Type:

Key at 10: 30 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 4th section rear

Throw Quantity:

6 2nd section rear

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Variable resistor provisions

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

250.0 ac at sea level

Rotor Through Connection Quantity:

1 4th section

Switch Actuator Indexing Position Quantity:

6 single actuator

Shaft Type:

Round, hollowed 1st actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

15.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0