

View Online at <https://aerobasegroup.com/nsn/5930-00-756-0355>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.375 inches single mounting facility

**Overall Length:**

6.500 inches

**Overall Height:**

2.310 inches

**Overall Width:**

1.970 inches

**Shaft Diameter:**

0.250 inches 1st actuator

**Shaft Length:**

0.500 inches 2nd actuator

**Nonturn Device Radius:**

0.530 inches at 10: 30 o'clock

**Individual Section Quantity:**

4

**Nonturn Device Type:**

Key at 10: 30 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 4th section rear

**Throw Quantity:**

6 2nd section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Features Provided:**

Variable resistor provisions

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

250.0 ac at sea level

**Rotor Through Connection Quantity:**

1 4th section

**Switch Actuator Indexing Position Quantity:**

6 single actuator

**Shaft Type:**

Round, hollowed 1st actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

15.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load dc at sea level

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0