

View Online at <https://aerobasegroup.com/nsn/5930-00-756-0410>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.250 inches single mounting facility

**Overall Length:**

Between 1.381 inches and 2.229 inches

**Overall Height:**

1.000 inches

**Overall Width:**

0.938 inches

**First Flat Length:**

0.312 inches single actuator

**Flat Height:**

0.216 inches single actuator

**Shaft Diameter:**

0.248 inches single actuator and 0.251 inches single actuator

**Shaft Length:**

0.375 inches single actuator

**Nonturn Device Radius:**

0.375 inches at 12: 00 o'clock

**Individual Section Quantity:**

3

**Nonturn Device Type:**

Tab at 12: 00 o'clock

**Operating Temperature Range:**

-55.0/+85.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section rear

**Throw Quantity:**

8 each section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Shaft Flat/slot Angular Location:**

0.270 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:**

8 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Detent Rotational Torque Range:**

+2.000/+4.000 inch-pounds single actuator

**Contact Load Current Rating:**

1.0 amperes resistive load ac at sea level

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

Tap, circular frame

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0