

View Online at <https://aerobasegroup.com/nsn/5930-00-756-6377>

Thread Class:

2a single mounting facility

Thread Length:

0.340 inches single mounting facility

Overall Length:

4.120 inches

Overall Height:

1.280 inches

Overall Width:

0.925 inches

Shaft Diameter:

0.125 inches single actuator

Shaft Length:

1.000 inches single actuator

Nonturn Device Radius:

0.250 inches at 6: 00 o'clock

Individual Section Quantity:

8

Nonturn Device Type:

Pin at 6: 00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Cam actuated

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Cam Actuated Switch Contact Arrangement:

1 pole, double throw, one position momentary each switch each section in-line

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Turret

Contact Switching Action:

Breaks before makes each section in-line

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level and 5.0 amperes inductive load ac at sea level

Style Designator:

In-line, cam actuated

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0