

View Online at <https://aerobasegroup.com/nsn/5930-00-757-3129>

**Thread Length:**

0.375 inches single mounting facility

**Overall Length:**

Between 1.281 inches and 1.595 inches

**Overall Height:**

Between 1.782 inches and 2.094 inches

**Overall Width:**

Between 1.531 inches and 2.031 inches

**First Flat Length:**

0.234 inches single actuator and 0.266 inches single actuator

**Shaft Diameter:**

0.248 inches single actuator and 0.251 inches single actuator

**Shaft Length:**

0.547 inches single actuator and 0.579 inches single actuator

**Nonturn Device Radius:**

0.515 inches at 3:00 o'clock and 0.547 inches at 3:00 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Tab at 3:00 o'clock

**Operating Temperature Range:**

-65.0/+85.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Shaft Flat/slot Angular Location:**

135.0 degrees from nonturn device single actuator

**Rotor Through Connection Quantity:**

1 single section

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Detent Rotational Torque Range:**

+20.000/+96.000 inch-ounces single actuator

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0