

View Online at <https://aerobasegroup.com/nsn/5930-00-757-3722>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.427 inches single mounting facility and 0.447 inches single mounting facility

**Width Between Flats:**

0.175 inches single actuator

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

3.540 inches

**First Flat Length:**

0.437 inches single actuator

**Shaft Diameter:**

0.248 inches single actuator and 0.252 inches single actuator

**Shaft Length:**

1.470 inches single actuator

**Overall Diameter:**

Between 1.350 inches and 1.410 inches

**Nonturn Device Radius:**

0.432 inches at 12: 00 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Slotted bushing at 12: 00 o'clock

**Operating Temperature Range:**

-65.0/+160.0 degrees fahrenheit

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

4 single section rear

**Throw Quantity:**

3 single section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Shaft Type:**

Round, milled, spring slit single actuator

**Terminal Type:**

Wire lead

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Detent Rotational Torque Range:**

+2.000/+3.000 inch-pounds single actuator

**Contact Load Current Rating:**

200.0 milliamperes resistive load dc at sea level and 500.0 milliamperes inductive load dc at sea level

**Special Features:**

Flap control

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0