

View Online at <https://aerobasegroup.com/nsn/5930-00-757-9704>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.370 inches and 0.380 inches

**Body Length:**

Between 0.765 inches and 0.797 inches

**Body Width:**

Between 0.234 inches and 0.266 inches

**Body Height:**

Between 0.468 inches and 0.500 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.083 inches and 0.093 inches

**Actuator Style:**

Roller arm

**Actuator Roller Width:**

Between 0.109 inches and 0.141 inches

**Maximum Voltage Rating In Volts:**

250.0 ac

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

18.0 ounces

**Switch Actuating Force:**

26.0 ounces

**Actuator Movement:**

Between 0.422 pretravel inches and 0.040 overtravel inches and 0.050 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive ac

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0