NSN 5930-00-758-4634

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-758-4634

Overall Length:
3.500 inches
Overall Height:
4.562 inches
Overall Width:
4.343 inches
Body Height:
4.562 inches
Unthreaded Mounting Hole Diameter:
0.203 inches
Distance Between Mounting Facility Centers:
2.250 inches
Pressure Switch Type:
Gage
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Electrical access port
Thready Qty Per Inch (tpi):
18 single pressure connection
Contact Action Stimulus:
Decrease
Proof Pressure:
60.00 pounds per square inch
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Tab w/screw
Contact Load Current Rating:
10.0 amperes resistive load second voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+0.40/+17.80 actuation point pounds per square inch and +0.60/+18.00 deactuation point pounds per square inch
Contact Adjustment Type:

Contact Voltage Rating In Volts:

External deactuation point screw and external actuation point screw

480.0 ac at sea level first voltage

NSN 5930-00-758-4634 Pressure Switch - Page 2 of 2



Pressure Connector Type:
Plain, threaded internal single connection
Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular
Thread Series Designator:
Npt single pressure connection
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0