NSN 5930-00-758-4864

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-758-4864

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.940 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Overall Height:

1.592 inches

Overall Width:

0.687 inches

Body Length:

1.940 inches

Body Width:

0.687 inches

Body Height:

1.040 inches

Unthreaded Mounting Hole Diameter:

0.169 inches

Actuator Length:

1.026 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

1.172 inches

Actuator Roller Diameter:

0.375 inches

Actuator Roller Width:

0.150 inches

Actuator Adapter Style:

Roller arm

Maximum Voltage Rating In Volts:

480.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.2 ounces

Switch Actuating Force:

Between 2.5 ounces and 6.5 ounces

NSN 5930-00-758-4864

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Test Data Document:

18876-10658194 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0