NSN 5930-00-758-4864

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-758-4864

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
1.940 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Overall Height:
1.592 inches
Overall Width:
0.687 inches
Body Length:
1.940 inches
Body Width:
0.687 inches
Body Height:
1.040 inches
Unthreaded Mounting Hole Diameter:
0.169 inches
Actuator Length:
1.026 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
1.172 inches
Actuator Roller Diameter:
0.375 inches
Actuator Roller Width:
0.150 inches
Actuator Adapter Style:
Roller arm
Maximum Voltage Rating In Volts:
480.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
1.2 ounces
Switch Actuating Force:

Between 2.5 ounces and 6.5 ounces

NSN 5930-00-758-4864

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Test Data Document:

18876-10658194 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0