

View Online at <https://aerobasegroup.com/nsn/5930-00-758-5190>

Thread Class:

2a

Body Style:

Bushing mounted

Bushing Length:

0.250 inches

Body Length:

0.500 inches

Body Width:

Between 0.312 inches and 0.316 inches

Body Height:

Between 0.400 inches and 0.420 inches

Actuator Diameter:

0.200 inches

Actuator Height:

0.275 inches

Actuator Color:

White single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

F-4 phantom, c-135 stratolifter, c-130 hercules, e-3a awacs, f-16 aircraft. H-53 super jolly helicopter. F-4, f-15, f-16, f-111, b-52, b-1 mx peacekeeper missile support equipment. Lgm-30 minuteman missile, mx peacekeeper missile. Ground wave emergency network (gwen). Radio an/grc-171 (v) 4. Consolidated space operations center.

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 1.000 amperes resistive ac

Special Features:

Weapon system essential

Precious Material And Location:

Contacts gold

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Specification Data:

80063-a3089382-1 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0