# NSN 5930-00-758-6515

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-758-6515

# **Thread Class:**

2a single mounting facility

## Thread Length:

0.375 inches single mounting facility

# **Overall Length:**

3.219 inches

#### **Overall Height:**

1.531 inches

#### **Overall Width:**

1.312 inches

#### Shaft Diameter:

0.250 inches single actuator

### Shaft Length:

2.375 inches single actuator

#### **Nonturn Device Radius:**

# 0.437 inches at 3: 00 o'clock

### Individual Section Quantity:

1

# Nonturn Device Type:

Tab at 3: 00 o'clock

## **Operating Tempurature Range:**

-25.0/+85.0 degrees celsius

## Switch Contact Basic Design:

Nonpile-up symmetrical

#### Pole Quantity:

1 single section front

### **Throw Quantity:**

12 single section rear

### Mounting Method:

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

### **Contact Voltage Rating In Volts:**

28.0 dc at sea level

### Switch Actuator Indexing Position Quantity:

12 single actuator

### Shaft Type:

Round, breakoff single actuator

### **Terminal Type:**

Tab, solder lug

### **Contact Switching Action:**

Breaks before makes single section front

# NSN 5930-00-758-6515

Rotary Switch - Page 2 of 2



# Switch Actuator Positioning Increment:

30.0 degrees single actuator

## Switch Actuator Stop Device Type:

Fixed-adjustable stops single actuator

## **Contact Load Current Rating:**

1.0 amperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

# **Thread Series Designator:**

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A052b0