## NSN 5930-00-759-5125

Sensitive Switch - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5930-00-759-5125

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Body Length:
1.810 inches
Body Width:
0.640 inches
Body Height:
1.130 inches
Unthreaded Mounting Hole Diameter:
0.145 inches
Actuator Length:
1.500 inches
Actuator Style:
Leaf
Actuator Width:
0.190 inches
Actuator Free Position Height:
0.312 inches
Maximum Voltage Rating In Volts:
250.0 ac
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Switch Release Force:
1.0 ounces
Switch Actuating Force:
6.0 ounces
Actuator Movement:
0.250 pretravel inches and 0.187 overtravel inches and 0.062 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
15.000 amperes resistive ac
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:

## NSN 5930-00-759-5125

Sensitive Switch - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A053a0